DESSO

Technical Specification

Desso Axminster Dec B-090-070

CONSTRUCTION:	Gripper Axminster
FIBER:	80% Wool / 20% Nylon
YARN PLY:	3/40 (Dewsbury)
TWIST COEFFICIENT:	3.7 Twists per inch
DYE METHOD:	Skein Dyed
LIGHT FASTNESS:	5-7 (ISO 105-B02)
WATER FASTNESS:	4-5 (ISO 105-E01)
RUB TEST:	3-5 (ISO 105-X12)
ROWS:	09 per inch
PITCH:	07 per inch
PILE HEIGHT:	.276"
TOTAL THICKNESS:	.360"
PILE WEIGHT:	45,6 oz. s/y
TOTAL WEIGHT:	70,0 oz. s/y
BACKING:	100% Synthetic
SECONDARY BACKING:	Fire Retardent Latex
WIDTH:	400 cms (13'2")
CLASSIFICATION:	Heavy Contract
FLAMMABILITY:	ASTM E648: Class 1; >0.5W/cm2 ASTM E662: < 300 ASTM D2859: Pass

All specifications subject to normal manufacturing tolerances

Desso (USA) Inc., 4641 West Chester Pike, Newtown Square, PA 19073
Phone: 800-368-1515 Fax: 610-356-6774 e-mail: dessousa@itnt.com
Local: (877)820-2343 Fax (603)954-5918 e-mail: BWalterDesso@aol.com